

# CASA FLOORS

LUXURY



PVC  
FLOORING



creating better environment...



VIRGIN  
MATERIAL

DURABILITY

# CASA FLOORS



# PVC FLOORING

**Size:** 152.4mm x 914.4 mm, (6"x 36")

**Thickness:** 1.5mm

**Wear Layer:** 0.1mm

**Size:** 152.4mm x 914.4 mm, (6"x 36")

**Thickness:** 1.5mm

**Wear Layer:** 0.1mm

**Size:** 152.4mm x 914.4 mm, (6"x 36")

**Thickness:** 1.5mm

**Wear Layer:** 0.1mm



5100



5101



5102



**CASA FLOORS**  
creating better environment

# PVC FLOORING

**Size:** 152.4mm x 914.4 mm, (6"x 36")

**Thickness:** 1.5mm

**Wear Layer:** 0.1mm

**Size:** 152.4mm x 914.4 mm, (6"x 36")

**Thickness:** 1.5mm

**Wear Layer:** 0.1mm

**Size:** 152.4mm x 914.4 mm, (6"x 36")

**Thickness:** 1.5mm

**Wear Layer:** 0.1mm



5103



5104



5105



**CASA FLOORS**  
creating better environment

# PVC FLOORING

**Size:** 152.4mm x 914.4 mm, (6"x 36")

**Thickness:** 1.5mm

**Wear Layer:** 0.1mm

**Size:** 152.4mm x 914.4 mm, (6"x 36")

**Thickness:** 1.5mm

**Wear Layer:** 0.1mm

**Size:** 152.4mm x 914.4 mm, (6"x 36")

**Thickness:** 1.5mm

**Wear Layer:** 0.1mm



5106



5107



5108



**CASA FLOORS**  
creating better environment

# PVC FLOORING

**Size:** 152.4mm x 914.4 mm, (6"x 36")

**Thickness:** 1.5mm

**Wear Layer:** 0.1mm

**Size:** 152.4mm x 914.4 mm, (6"x 36")

**Thickness:** 2mm

**Wear Layer:** 0.2mm

**Size:** 152.4mm x 914.4 mm, (6"x 36")

**Thickness:** 2mm

**Wear Layer:** 0.2mm



5109



5200



5201



**CASA FLOORS**  
creating better environment

# PVC FLOORING

**Size:** 152.4mm x 914.4 mm, (6"x 36")

**Thickness:** 2mm

**Wear Layer:** 0.2mm

**Size:** 152.4mm x 914.4 mm, (6"x 36")

**Thickness:** 2mm

**Wear Layer:** 0.2mm

**Size:** 152.4mm x 914.4 mm, (6"x 36")

**Thickness:** 2mm

**Wear Layer:** 0.2mm



5202



5203



5204



**CASA FLOORS**  
creating better environment



## Technical specifications

Allura Click meets the requirements of EN-ISO 10582

	Total thickness	EN-ISO 24346	1.5mm & 2mm
	Wearlayer thickness	EN-ISO 24340	0.1mm & 0.2mm
	Collection size		38
	Domestic use	EN-ISO 10874	23
	Commercial use	EN-ISO 10874	33
	Plank size	EN-ISO 24342	152.4mm x 914.4 mm, (6"x 36")
	Packaging per carton planks		1.5mm Thickness with 32 pcs/ box & 2mm Thickness with 24 pcs/ box
	Squareness and straightness	EN-ISO 24342	< 400 mm < 0.25 mm > 400 mm < 0.35 mm
	Total weight	ISO 23997	(1.5mm Thickness)3kgs/m <sup>2</sup> & (2mm Thickness)4kgs/m <sup>2</sup>
	Wearlayer binder content	EN-ISO 10582	Type 1
	Slip resistance	DIN 51130	R10
	Acoustical impact noise reduction	EN ISO 717-2	7 dB / 15 dB in combination with Forbo underlay
	Castor chair continuous use	ISO 4918	Good, with and without Forbo underlay
	Residual indentation <i>Typical value</i>	ISO 24343-1	≤ 0.10 mm ~ 0.05 mm
	Light fastness	ISO 105-B02	≥ 6
	VOC emissions	ISO 16000-9	≤ 160 µg/m <sup>3</sup>
	Resistance to chemicals	EN-ISO 26987	Very good
	Dimension stability (after exp. to heat)	EN-ISO 23999	≤ 0.05%
			EN 14041 <b>CE</b> 0200132_DoP_701
	Allura Click meets the requirements of EN 14041		
	Reaction to fire	EN 13501	B <sub>f</sub> -s1 with and without Forbo underlay
	Slip resistance	EN 13893	DS - µ > 0.30
	Thermal conductivity	EN 12524	0.25 W/mK
	Body voltage	EN 1815	< 2 kV

# CASA FLOORS



TO STAY CONNECTED  
FOLLOW US



[www.casadecorative.in](http://www.casadecorative.in)